

MPS-H Series

Off Grid Solar Inverter



Features

- Pure sine wave output
- Output power factor 1.0
- Programmable supply priority for PV, battery or Grid
- User-adjustable charge current and voltage
- Wide PV input range (120Vdc -500Vdc), 110A MPPT SCC
- Working without batteries in sunny day
- WiFi Monitoring Function (optional)
- Anti-dusk kit for harsh environment(optional)
- LCD remote control with 10 meters wire(optional)
- PV and electricity complementary
- Use with lithium batteries

System Diagram

Operation with battery connected

Solar Power and AC Power available



Solar Power and AC Power not available



Operation without battery connected

Solar Power available



AC Power available



Product Data Sheet

MODEL	MPS-3500H	MPS-5500H
Rated Power	3500VA/3500W	5500VA/5500W
INPUT		
Voltage	230VAC	
Selectable Voltage Range	170-280VAC(for personal computers) 90-280VAC(for home appliances)	
Frequency Range	50Hz/60Hz (Auto sensing)	
OUTPUT		
AC Voltage Regulation (Batt.Mode)	230VAC±5%	
Surge power	7000VA	11000VA
Efficiency(Peak) PV to INV	97%	
Efficiency(Peak) BAT to INV	94%	
Transfer Time	10ms (for personal computers) 20ms (for home appliances)	
Wave form	Pure Sine Wave	
BATTERY & AC CHARGER		
Battery Voltage	24VDC	48VDC
Floating Charge Voltage	27VDC	54VDC
Overcharge Protection	33VDC	63VDC
Maximum charge current	80A	80A
SOLAR CHARGER		
MAX.PV Array Power	5000W	6000W
MPPT Range@ Operating Voltage	120-500VDC	
Maximum PV Array Open Circuit Voltage	500VDC	
Maximum Charging Current	110A	
Maximum Efficiency	98%	
PHYSICAL		
Dimension.D*W*H(mm)	472*297*129	
Net Weight (kgs)	13kg	14kg
Communication Interface	RS485/RS232(Standard) LCD remote/WIFI(Optional)	
OPERATING ENVIRONMENT		
Humidity	5% to 95% Relative Humidity(Non-condensing)	
Operating Temperature	0°C to 55°C	
Storage Temperature	-15°C to 60°C	

smart
lexron smart technology systems

